

SWITCHED & SWITCHED ULTRA 230/400V PDUs

MAXIMIZE YOUR
INFRASTRUCTURE CAPACITY



16A or 32A 230/400 Volt
4P 5W, PIN & SLEEVE CONNECTORS



Remote Monitoring & Switching
GRCMBN243-102IK3PS56-O

Remote Outlet Monitoring & Switching
GRCUBN243-102IK3PS56-O

Remote Monitoring & Switching
GRCMN243-103IK3PS56-O

Remote Outlet Monitoring & Switching
GRCUN243-103IK3PS56-O

QUANTITY OF INPUTS	1
AMPS	16
VOLTS	230 / 400
OUTPUT VOLTAGE	230
TOTAL RECEPTACLE QTY	24
RECEPTACLE TYPE / QTY	C-13 / 21
RECEPTACLES PER BREAKER AND/OR PHASE	7
RECEPTACLE TYPE / QTY	C-19 / 3
RECEPTACLES PER BREAKER AND/OR PHASE	1
REMOTE POWER SWITCHING AT THE RECEPTACLE LEVEL	YES
MAGNETIC CIRCUIT BREAKER / ON-OFF SWITCH WITH INTEGRAL SWITCH GUARD	N/A
BREAKER AMPERAGE / QTY	N/A
BREAKER POLE CONFIGURATION	N/A
POWER MONITORING	PHASE (X,Y,Z)
AMPS PER OUTLET ALARMING	NO
kWh & WATTS MONITORING PER OUTLET	NO
ENVIRONMENTAL MONITORING - REMOTE SENSOR JACKS	2
ETHERNET CONNECTION	1
REMOTE DISPLAY (GRSD2X8)	1
3M POWER CORD	1
IEC 60309 230/400 VOLT, PIN & SLEEVE CONNECTOR	16A 4P / 5W
FULL-LENGTH VERTICAL MOUNTING BRACKET	YES
TOOLLESS MOUNTING HARDWARE - CENTER TO CENTER SPACING (mm)	1556 & 1645
BREAKER DOGHOUSE - 33mm DEPTH	N/A
DIMENSIONS L	1683
DIMENSIONS W	64
DIMENSIONS D	58



REMOTE POWER CONTROL PLUS POWER & ENVIRONMENTAL MONITORING

The GRCU-O Switched Ultra series is Geist's most feature rich power distribution unit. It is Ethernet enabled, with an on-board web server that tracks the GRCU-O's configuration and collected data. Voltage, Amps, and Power Factor are monitored by the GRCU-O at each input circuit, while the GRCU-O monitors current, kWh and watts at each circuit and at each outlet. Optional sensors (such as temperature, airflow, etc.) are easily added. The automated graphing feature shows changes that happen over time. GRCU-O's most distinctive feature is remote switching & monitoring capability for each individual outlet. This allows the IT manager to cycle the power of a locked-up server from the website.

GRSD2X8 DISPLAY



SPECIFICATION

- Internal Power Sensors
 - Volts RMS: 80-280 VAC
 - Amps RMS: 0-32A
- Ethernet Connection Jack
- Power On Indicator
- Activity Indicator
- Idle Indicator
- Software Reset Button
- Remote Display (RSD2X8) Jack
- External Sensor Ports
 - Two RJ12 Jacks
 - Connect up to 16 Remote Sensors via Splitters
- CE® Compliant