

# Plug & Receptacle Configuration Chart



NEMA										IEC									
AMP	VOLT	STRAIGHT-BLADE PLUG	STRAIGHT-BLADE RECEPTACLE	AMP	VOLT	STRAIGHT-BLADE PLUG	STRAIGHT-BLADE RECEPTACLE	AMP	VOLT	STRAIGHT-BLADE PLUG	STRAIGHT-BLADE RECEPTACLE	AMP	VOLT	POWER INLET	POWER RECEPTACLE	AMP	VOLT	POWER INLET	POWER RECEPTACLE
15	125			20	250			20	250			20/16*	125 OR 250			20/16*	125 OR 250		
20	125													PIN & SLEEVE					
AMP	VOLT	TWIST-LOCK PLUG	TWIST-LOCK RECEPTACLE	AMP	VOLT	TWIST-LOCK PLUG	TWIST-LOCK RECEPTACLE	AMP	VOLT	TWIST-LOCK PLUG	TWIST-LOCK RECEPTACLE	AMP	VOLT	PIN & SLEEVE		AMP	VOLT	PIN & SLEEVE	
15	125			30	125 / 250			30	125 / 250			30	125 / 250			60/63*	250/230*		
20	125			20	120/208 x 3-WYE			20	120/208 x 3-WYE			20	120/208 x 3-WYE			60	250		
30	125			30	120/208 x 3-WYE			30	120/208 x 3-WYE			30	120/208 x 3-WYE			20/16*	230/400* x 3-WYE		
20	250			30	250 x 3-DELTA			30	250 x 3-DELTA			30	250 x 3-DELTA			30/32*	230/400* x 3-WYE		
30	250			AMP	VOLT	CALIFORNIA STYLE		AMP	VOLT	CALIFORNIA STYLE		AMP	VOLT						
20	125 / 250			50	250 x 3-DELTA			50	250 x 3-DELTA			50	250 x 3-DELTA			50	250 x 3-DELTA		

\* Rating for CE products